

## Fittings / LED Floodlights


# Skyline Slim+ 10W LED Floodlight with PIR - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- PIR Over-ride function.
- Average 8M detection range for PIR Floods.
- Separately tested IP65 PIR.

## Technical Specification



Without PIR Symmetric									
	10W	20W	30W	40W	50W	60W	80W	120W	150W
A	146mm	146mm	146mm	146mm	146mm	146mm	146mm	146mm	146mm
B	112mm	120mm	136mm	172mm	225mm	276mm	300mm	300mm	355mm
C	31mm	33mm	34mm	44mm	48mm	60mm	60mm	60mm	60mm

Asymmetric Without PIR				
	10W	20W	30W	40W
A	135mm	135mm	135mm	135mm
B	154mm	235mm	277mm	302mm
C	48mm	60mm	60mm	60mm

With PIR Symmetric				
	10W	20W	30W	40W
A	176mm	185mm	200mm	239mm
B	112mm	120mm	137mm	172mm
C	68mm	68mm	72mm	72mm

**Product Code**

10985

## Reference

**Guarantee**

5 Years

**EAN**

5013588109855

**Commodity Code**

9405423990

**Country of Origin**

CN

**UNSPSC Code**

39111626

## Technical Specification

Volts (V)	240
Watts (W)	10
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	1200
Life Hours	50000
Beam Angle	110°
CRI (ra)	80
Switching Cycles	25000
Frequency (Hz)	50/60
LED Drive Current	130mA
Energy Consumption (kWh/1000h)	10
IP Rating	IP65
Impact Protection	IK8

## Dimensions

Height (mm)	176
Width (mm)	112
Depth (mm)	68

## Packaging Information

Single Carton Height (mm)	115
Single Carton Width (mm)	68
Single Carton Depth (mm)	181
Single Carton Weight (kg)	0.49543
Individual Volume	0.00142
Outer Box Qty	12
Outer Box Height (mm)	425
Outer Box Width (mm)	236
Outer Box Depth (mm)	187
Outer Box Weight (kg)	6.37895