

Fittings / LED Floodlights


Skyline Slim+ 30W LED Floodlight with PIR - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- PIR Over-ride function.
- Average 8M detection range for PIR Floods.
- Separately tested IP65 PIR.

Technical Specification



Without PIR Symmetric									
	15W	20W	30W	40W	50W	60W	80W	120W	150W
A	114mm	142mm	158mm	168mm	178mm	188mm	216mm	270mm	300mm
B	112mm	120mm	136mm	122mm	225mm	276mm	300mm	350mm	350mm
C	31mm	33mm	34mm	44mm	48mm	60mm	60mm	60mm	60mm

Asymmetric Without PIR					
	30W	40W	50W	60W	80W
A	114mm	116mm	116mm	116mm	140mm
B	124mm	235mm	277mm	302mm	352mm
C	48mm	60mm	60mm	60mm	60mm

With PIR Symmetric					
	15W	20W	30W	40W	70W
A	176mm	185mm	200mm	239mm	300mm
B	112mm	120mm	137mm	170mm	220mm
C	68mm	68mm	72mm	72mm	72mm

Product Code

10987

Reference

Guarantee

5 Years

EAN

5013588109879

Commodity Code

9405423990

Country of Origin

CN

UNSPSC Code

39111626

Product Application

Exterior Lighting

Product Category

Floodlight

Technical Specification

Watts (W)	30
Equivalent Watts (W)	240
Volts (V)	240
Colour Temp (K)	4000
Lumens (lm)	3600
Lumens per Watt (lm/W)	120
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	305mA
Energy Consumption (kWh/1000h)	30
Life Hours	50000
Switching Cycles	25000
Impact Protection	IK8
IP Rating	IP65

Dimensions

Height (mm)	200
Width (mm)	137
Depth (mm)	72

Packaging Information

Height (mm)	200
Width (mm)	137
Depth (mm)	72
Individual Product Weight (kg)	0.6
Single Carton Height (mm)	139
Single Carton Width (mm)	68
Single Carton Depth (mm)	203
Single Carton Weight (kg)	0.68292
Individual Volume	0.00192
Outer Box Qty	12
Outer Box Height (mm)	425
Outer Box Width (mm)	284
Outer Box Depth (mm)	209
Outer Box Weight (kg)	8.7296
Outer Box Volume	0.02523