



Fittings / LED Floodlights


150/225/300W Skyline Virtus Wattage Switchable Asymmetric Floodlight - 4000K



Designed and engineered in the UK specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight, wattage switchable as standard with a 50,000 hour lifespan, 7 year warranty and 2 year on site warranty.

- Wattage Switchable
- Perfect for sports, building facade's, landscape, security & car park lighting
- Asymmetric distribution, low light pollution
- Aerodynamic, streamlined design for reduced windage
- Air pressure equalisation feature to eliminate capillary effect
- Nichia GRT-V1 LED
- Surge protected 10,000V
- Fully encapsulated IP54 TUV certified driver
- Supplied pre-flexed (1.5M)
- Robust construction, supplied with standard universal mounting bracket

Technical Specification



| Product Code | 11491 |
|-------------------|---------|
| Reference | |
| Guarantee | 7 Years |
| Country Of Origin | CN |

www.belllighting.co.uk







Technical Specification

| Volts (V) | 110-240 |
|--------------------------------|-------------|
| Watts (W) | 150/225/300 |
| Colour Temp (K) | 4000 |
| Lumens (lm) | 22400-46050 |
| Life Hours | 50,000 |
| CRI (Ra) | 80 |
| Switching Cycles | 100,000 |
| Frequency (Hz) | 50/60 |
| Energy Consumption (kWh/1000h) | 132 |
| IP Rating | IP66 |
| Dimensions | |
| Height (mm) | 495 |
| Width (mm) | 417 |
| Depth (mm) | 75 |
| Packaging Information | |
| Single Carton Height (mm) | 52.5 |
| Single Carton Width (mm) | 45 |
| Single Carton Depth (mm) | 11.5 |
| Single Carton Weight (KG) | 7.1 |
| | |

www.belllighting.co.uk

