



Fittings / LED Panels

Arial Plus Multi Backlit LED Panel - 25mm 600x600mm, 4000K, UGR<19, White



The Arial Plus Multi is our leading wattage switchable panel. With a high lumen output of up to 125 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus Multi can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- · High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- 0-10V Dimming or DALI Dimming options available
- · White finish
- · Anti-twist frame
- Emergency panels with 5 year battery warranty available
- CCT option available

Technical Specification

Product Code	11748	

Reference

Guarantee	7 Years
EAN	5013588117485
Commodity Code	9405409990
Country Of Origin	CN
UNSPSC Code	39111544

E: sales@belllighting.co.uk
T: 01924 893380







Technical Specification

Volts (V)	220-240
Watts (W)	20/26/30/36
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	2400-4100
Life Hours	50,000
CRI (Ra)	85
Switching Cycles	25,000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	595
Width (mm)	595
Depth (mm)	25

E: sales@belllighting.co.uk **T:** 01924 893380

