BELLlighting

Olluminalinear

Illumina Linear 100W LED UGR Symmetric High Bay - 4000K

Part Code: 11307

The Illumina Linear offers a sleek design coupled with high performance. Perfect for high ceiling warehouses, industrial facilities, exhibition centres, shopping malls, sports halls & stadiums.

- TUV Isolated Driver
- Suitable for High Bay and Low Bay applications 4-12m
- Plug-in PIR and Microwave sensors
- Sensor parameters set by remote control
- Specially designed for low glare sports and warehouse lighting













Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk

BELLlighting

Olluminalinear



ngs / LED Warehouse Lighting
nmercial / Industrial / Warehousing
ars
3588113074
5423990

Technical Specification		
Watts (W)	100	
Equivalent Watts (W)	250	
Volts (V)	110/264	
Colour Temp (K)	4000	
Lumens (lm)	13764	
Lumens per Watt (lm/W)	138	
CRI (ra)	85	
Frequency (Hz)	50/60	
LED Drive Current	122mA	
Energy Consumption (kWh/1000h)	100	
Life Hours	50000	
Switching Cycles	100000	
Impact Protection	IK8	
IP Rating	IP65	

Packaging Information		
Height (mm)	113	
Width (mm)	118	
Length (mm)	717	
Individual Product Weight (kg)	3.2	
Single Carton Height (mm)	775	
Single Carton Width (mm)	130	
Single Carton Depth (mm)	155	
Single Carton Weight (kg)	3.67	
Individual Volume	0.01561625	
Outer Box Height (mm)	775	
Outer Box Width (mm)	130	
Outer Box Depth (mm)	155	
Outer Box Weight (kg)	3.67	
Outer Box Volume	0.01561625	
UNSPSC Code	39111546	
Minimum Order Quantity	1	

Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk

BELLlighting

Olluminalinear

Additional Information				
Flex	1.5m			
Accessories				
11325	Adjustable 60° Bracket for the Illumina Linear UGR LED High Bay			
11324	Suspension Kit for the Illumina Linear UGR LED High Bay			

Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk

The information shown above was correct at time of publication. Please refer to our Terms & Conditions of Sale for further detail.