

Luminaires

25W Dura LED Anti Corrosive Batten - 4000K, Single 1500mm

BEL06710



20W DURA LED ANTI CORROSIVE BATTEN 4000K

	BEL06710
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
With mounting material	Yes
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	EV000494
Housing material	Plastic
Housing colour	Grey
Material cover	Plastic matt/satinized
Type of grid	None
Voltage type	AC
Nominal voltage	220 - 240 V
With control gear	Yes
Dimmable	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP), front side	IP66
Impact strength	IK10
Emergency power supply system	None

25W Dura LED Anti Corrosive Batten - 4000K, Single 1500mm

	BEL06710
Suitable for emergency lighting	No
Emergency function monitoring system	None
With switch	No
With presence detector	No
With movement sensor	No
With light sensor	No
Suitable for lamp power	25 - 25 W
Luminaire efficacy	169 - 169 lm/W
Max. system power	25 W
Rated luminous flux according to IEC 62722-2- 1	4224 - 4224 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Power factor	0.97
Width	90 mm
Height/depth	90 mm
Length	1530 mm
Connection type	Push-in clamp
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BELL LIGHTING
Art. N°	BEL06710
Sales unit	pc
EAN PCE	5013588067100
EAN QTY PCE	1
Intrastat code	85392992