

Luminaire

52W Dura LED Anti Corrosive Batten 4000K Double 1500mm (5ft)

BEL06716



52W Dura LED Anti Corrosive Batten 4000K Double 1500mm (5ft)

	BEL06716
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
With mounting material	Yes
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	2
Lamp holder	EV000494
Housing material	Plastic
Material cover	Plastic matt/satinized
Type of grid	None
Voltage type	AC
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off (trailing edge)	No

52W Dura LED Anti Corrosive Batten 4000K Double 1500mm (5ft)

	BEL06716
Dimming phase cut-on (leading edge)	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP), front side	IP66
Impact strength	IK10
Emergency power supply system	None
Suitable for emergency lighting	No
Emergency function monitoring system	None
With switch	No
With presence detector	No
With movement sensor	No
With air slots	No
Filament test according to IEC 60695-2-11	None
Suitable for lamp power	52 - 52 W
Luminaire efficacy	163 - 163 lm/W
Max. system power	52 W
Rated luminous flux according to IEC 62722-2- 1	8448 - 8448 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Power factor	0.97
Width	125 mm
Height/depth	90 mm
Length	1530 mm
Connection type	Push-in clamp
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No
Brand	BELL LIGHTING
Art. N°	BEL06716
Sales unit	pc
EAN PCE	5013588067162
EAN QTY PCE	1
Intrastat code	85392992