

Luminares

100-200W Illumina Muto LED Wattage Switchable High Bay - 120° Lens, 4



100-200W Illumina Muto LED Wattage Switchable High Bay - 120° Lens, 4000K

	BEL08945V2
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Voltage type	AC
Nominal voltage	220 - 240 V
Nominal current	900 - 900 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Beam angle	> 80° - Extreme wide beam
Rated lifetime L70/B50 at 25 °C	30000 h
Degree of protection (IP)	IP65
Impact strength	IK08
Emergency power supply system	None
Emergency function monitoring system	None
Suitable for lamp power	100 - 200 W
Max. system power	200 W
Luminaire efficacy	117 - 117 lm/W
Rated luminous flux according to IEC 62722-2- 1	11735 - 23339 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Colour of light adjustable	No
Luminous flux adjustable	Positions
Height/depth	60 mm
Outer diameter	300 mm

100-200W Illumina Muto LED Wattage Switchable High Bay - 120° Lens, 4

Brand	BELL LIGHTING
Art. N°	BEL08945V2
Sales unit	pc
EAN PCE	5013588900155
EAN QTY PCE	1