

Luminaires

<p>The Illumina Linear offers a sleek design coupled with high perfor

BEL08950



The Illumina Linear offers a sleek design coupled with high performance. Perfect for high ceiling warehouses, industrial facilities, exhibition centres, shopping malls & stadiums.

	BEL08950
Suitable for suspended mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Voltage type	AC
Nominal voltage	110 - 264 V
Nominal current	120 - 120 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Asymmetric
Beam angle	41-80° - Wide beam
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP)	IP65
Impact strength	IK10
Max. system power	200 W
Luminaire efficacy	130 - 130 lm/W
Rated luminous flux according to IEC 62722-2- 1	26000 - 26000 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	137 mm
Height/depth	102 mm
Length	948 mm

<p>The Illumina Linear offers a sleek design coupled with high
perfor

Brand	BELL LIGHTING
Art. N°	BEL08950
Sales unit	pc
EAN PCE	5013588089508
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054099