# Luminaires

## 12/16/18/20W Arial Pro LED Downlight IP44 - CCT

BEL10952



12/16/18/20W Arial Pro LED Downlight IP44 - CCT

| | BEL10952 |
|---|---|
| **Suitable for surface mounting** | No |
| **Suitable for built-in mounting** | Yes |
| **Suitable for wall mounting** | No |
| **Suitable for suspended mounting** | No |
| **Suitable for ceiling mounting** | Yes |
| **Suitable for traverse mounting** | No |
| **Suitable for pedestal/floor mounting** | No |
| **Suitable for light-track mounting** | No |
| **Suitable for clamp-mounting** | No |
| **Suitable for low voltage cable system** | No |
| **Adjustability** | Not adjustable |
| **Lamp type** | LED not exchangeable |
| **With light source** | Yes |
| **Lamp holder** | None |
| **Voltage type** | AC |
| **Nominal voltage** | 220 - 500 V |
| **Nominal current** | 500 - 6000 mA |
| **Type of control gear** | LED operating device current-controlled |
| **With control gear** | Yes |
| **Beam angle** | > 80° - Extreme wide beam |
| **Light outlet** | Direct |
| **Rated lifetime L70/B50 at 25 °C** | 50000 h |
| **Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)** | 80 % |
| **Degree of protection (IP), front side** | IP44 |
| **Rated ambient temperature according to IEC 62722-2-1** | -5 - 144 °C |
| **Suitable for lamp power** | 12 - 240 W |
| **Max. system power** | 20 W |

*Documents and visuals are non-contractual, technical specifications are subject to change without notice.

# 12/16/18/20W Arial Pro LED Downlight IP44 - CCT

| | **BEL10952** |
|---|---|
| **Colour of light** | White |
| **Colour temperature** | 3000 - 35 K |
| **Colour of light adjustable** | Positions |
| **Colour rendering index CRI** | 80-89 |
| **Rated luminous flux according to IEC 62722-2- 1** | 1551 lm |
| **Luminaire efficacy** | 129 - 2885 lm/W |
| **Beam angle adjustable** | No |
| **Height/depth** | 117 mm |
| **Outer diameter** | 240 mm |

| | |
|---|---|
| **Brand** | BELL LIGHTING |
| **Art. N°** | BEL10952 |
| **Sales unit** | pc |
| **EAN PCE** | 5013588109527 |
| **EAN QTY PCE** | 1 |
| **Intrastat code** | 94054231 |

*Documents and visuals are non-contractual, technical specifications are subject to change without notice.