

Luminaires

100W SKYLINE SLIM ASYMMETRIC LEDFLOODLIGHT 4000K

BEL10977

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10977
With movement sensor	Yes
With presence detector	Yes
Movement sensor/presence detector technology	Passive infrared
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Aluminium
Nominal voltage	240 - 240 V
Nominal current	930 - 930 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Asymmetric
Light outlet	Direct
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	100 W
Emergency power supply system	None
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	13117 - 13117 lm
Luminaire efficacy	131 - 131 lm/W
Length	315 mm
Width	277 mm

100W SKYLINE SLIM ASYMMETRIC LEDFLOODLIGHT 4000K

	BEL10977
Height/depth	60 mm
Brand	BELL LIGHTING
Art. N°	BEL10977
Sales unit	pc
EAN PCE	5013588109770
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054239