

Luminaire

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

BEL10978



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10978
With movement sensor	Yes
With presence detector	Yes
Movement sensor/presence detector technology	Passive infrared
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Aluminium
Nominal voltage	240 - 240 V
Nominal current	1390 - 1390 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Asymmetric
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	10 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	150 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	19476 - 19476 lm
Luminaire efficacy	130 - 130 lm/W

<p>The Skyline Slim+ LED Floodlight is suitable for a wide range of
a

	BEL10978
Length	351 mm
Width	302 mm
Height/depth	60 mm

Brand	BELL LIGHTING
Art. N°	BEL10978
Sales unit	pc
EAN PCE	5013588109787
EAN QTY PCE	1
EAN C01	S10978090027420002
EAN QTY C01	2
Intrastat code	94054239