

Luminaires

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

BEL10980



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10980
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Nominal voltage	240 - 240 V
Nominal current	130 - 130 mA
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), rear side	EV006421
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	10 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	1397 - 1397 lm
Luminaire efficacy	140 - 140 lm/W
Length	134 mm
Width	112 mm

<p>The Skyline Slim+ LED Floodlight is suitable for a wide range of
a

	BEL10980
Height/depth	31 mm

Brand	BELL LIGHTING
Art. N°	BEL10980
Sales unit	pc
EAN PCE	5013588109800
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054239