

Luminaires

<p>The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small. **BEL10981**



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10981
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Nominal voltage	240 - 240 V
Nominal current	230 - 230 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	20 W
Emergency power supply system	None
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	2916 - 2916 lm
Luminaire efficacy	146 - 146 lm/W
Length	142 mm

<p>The Skyline Slim+ LED Floodlight is suitable for a wide range of
a

	BEL10981
Width	120 mm
Height/depth	33 mm

Brand	BELL LIGHTING
Art. N°	BEL10981
Sales unit	pc
EAN PCE	5013588109817
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054239