

Luminaires

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

BEL10982



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10982
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Aluminium
Nominal voltage	240 - 240 V
Nominal current	305 - 305 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	10 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	30 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	4432 - 4432 lm
Luminaire efficacy	148 - 148 lm/W
Length	158 mm
Width	136 mm
Height/depth	34 mm

<p>The Skyline Slim+ LED Floodlight is suitable for a wide range of
a

Brand	BELL LIGHTING
Art. N°	BEL10982
Sales unit	pc
EAN PCE	5013588109824
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054239