

Luminaire

30W Skyline Slim+ PIR LED Floodlight - 4000K

BEL10987



30W Skyline Slim+ PIR LED Floodlight - 4000K

	BEL10987
With movement sensor	Yes
With presence detector	Yes
Movement sensor/presence detector technology	Passive infrared
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Nominal voltage	240 - 240 V
Nominal current	305 - 305 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	10 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	30 W
Emergency power supply system	None
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	4432 - 4432 lm
Luminaire efficacy	148 - 148 lm/W
Length	200 mm

30W Skyline Slim+ PIR LED Floodlight - 4000K

	BEL10987
Width	137 mm
Height/depth	72 mm

Brand	BELL LIGHTING
Art. N°	BEL10987
Sales unit	pc
EAN PCE	501358810987;5013588109879
EAN QTY PCE	1
Intrastat code	85392992