

Luminares

200W Skyline Slim+ LED Floodlight -4000K

BEL10992

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

	BEL10992
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Nominal voltage	240 - 240 V
Nominal current	1850 - 1850 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	10 %
Degree of protection (IP), front side	IP65
Impact strength	IK08
Rated ambient temperature according to IEC 62722-2-1	-30 - 35 °C
Max. system power	200 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	25908 - 25908 lm
Luminaire efficacy	130 - 130 lm/W
Length	410 mm
Width	355 mm
Height/depth	60 mm

200W Skyline Slim+ LED Floodlight -4000K

Brand	BELL LIGHTING
Art. N°	BEL10992
Sales unit	pc
EAN PCE	5013588109923
EAN QTY PCE	1
EAN QTY C01	1
Intrastat code	94054910