

Luminaire

4/6W Firestay Duo LED CCT Wattage Switchable Fixed Downlight - BEL11370V2 Dim, P



4/6W Firestay Duo LED CCT Wattage Switchable Fixed Downlight - Dim, P&P, 60° Beam Angle - Lever
Tool-Free Termination - No Bezel

	BEL11370V2
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Voltage type	AC
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming phase cut-off (trailing edge)	Yes
Dimming phase cut-on (leading edge)	Yes
Light distribution	Symmetric
Beam angle	41-80° - Wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP), front side	IP65
Impact strength	IK07
Rated ambient temperature according to IEC 62722-2-1	-5 - 35 °C
With switch	Yes
Suitable for lamp power	4 - 6 W
Luminaire efficacy	136 - 164 lm/W
Max. system power	6 W
Rated luminous flux according to IEC 62722-2- 1	620 - 908 lm
Colour of light	White
Colour temperature	2700 - 6000 K

4/6W Firestay Duo LED CCT Wattage Switchable Fixed Downlight - Dim, P

	BEL11370V2
Colour rendering index CRI	80-89
Height/depth	34 mm
Outer diameter	90 mm
Built-in height/depth	34 mm
Built-in diameter	90 mm
Connection type	Push-in clamp
Luminous intensity	380 - 580 cd
Colour of light adjustable	Positions
Luminous flux adjustable	Positions
Beam angle adjustable	No

Brand	BELL LIGHTING
Art. N°	BEL11370V2
Sales unit	pc
EAN PCE	501358811370;5013588900025
EAN QTY PCE	1
Intrastat code	94054239