

Luminaires

Arial Multi Backlit LED Panel - 25mm 600x600mm, White, 4000K

BEL11740


Arial Multi Backlit LED Panel - 25mm 600x600mm, White, 4000K

	BEL11740
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	White
Material cover	Plastic, opal
Type of grid	None
Voltage type	AC
Nominal voltage	220 - 240 V
With control gear	Yes
Dimmable	Yes
Dimming 0-10 V	Yes
Dimming DALI	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP20
Rated ambient temperature according to IEC 62722-2-1	0 - 35 °C
Suitable for emergency lighting	Yes
Luminaire efficacy	138 - 138 lm/W
Max. system power	36 W
Rated luminous flux according to IEC 62722-2- 1	3081 - 4961 lm

Arial Multi Backlit LED Panel - 25mm 600x600mm, White, 4000K

	BEL11740
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	25 mm
Length	595 mm
Built-in length	595 mm
Built-in width	595 mm
Built-in height/depth	25 mm
Operation by Bluetooth	Yes
Compatible with Casambi	Yes

Brand	BELL LIGHTING
Art. N°	BEL11740
Sales unit	pc
EAN PCE	501358811740
EAN QTY PCE	1
Intrastat code	94054099