

Luminares

Arial Plus Multi Backlit High Output UGR<19 LED Panel - 25mm
600x600mm

BEL11764



Arial Plus Multi Backlit High Output UGR19 LED Panel - 25mm 600x600mm, White, CCT

	BEL11764
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming 0-10 V	Yes
Dimming DALI	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), rear side	IP40
Degree of protection (IP), front side	IP40
Rated ambient temperature according to IEC 62722-2-1	0 - 35 °C
Suitable for emergency lighting	Yes
Luminaire efficacy	124 - 131 lm/W

Arial Plus Multi Backlit High Output UGR<19 LED Panel - 25mm 600x600mm

	BEL11764
Max. system power	36 W
Rated luminous flux according to IEC 62722-2- 1	2580 - 4644 lm
Colour of light	White
Colour temperature	3000 - 6000 K
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	25 mm
Length	595 mm
Built-in length	595 mm
Built-in width	595 mm
Built-in height/depth	25 mm
Colour of light adjustable	Positions
Luminous flux adjustable	Positions
Beam angle adjustable	No

Brand	BELL LIGHTING
Art. N°	BEL11764
Sales unit	pc
EAN PCE	501358811764
EAN QTY PCE	1
Intrastat code	94054099