

Luminaires

**Arial Plus Multi Backlit High Output UGR<19 LED Panel - 25mm
1200x300**

BEL11772



Arial Plus Multi Backlit High Output UGR19 LED Panel - 25mm 1200x300mm - white - 4000K

	BEL11772
Suitable for ceiling mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming 0-10 V	Yes
Dimming DALI	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	10 %
Degree of protection (IP), front side	IP40
Rated ambient temperature according to IEC 62722-2-1	0 - 35 °C
Suitable for emergency lighting	Yes
Luminaire efficacy	129 - 134 lm/W
Rated luminous flux according to IEC 62722-2- 1	2685 - 4656 lm

Arial Plus Multi Backlit High Output UGR<19 LED Panel - 25mm 1200x300

	BEL11772
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	295 mm
Height/depth	25 mm
Length	1195 mm
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BELL LIGHTING
Art. N°	BEL11772
Sales unit	pc
EAN PCE	501358811772
EAN QTY PCE	1
Intrastat code	94054099