

Luminaires

Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, white, 4000K

BEL11780



Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, white, 4000K

	BEL11780
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	White
Material cover	Plastic, opal
Type of grid	White
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming 0-10 V	Yes
Dimming DALI	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP65
Rated ambient temperature according to IEC 62722-2-1	0 - 35 °C
Luminaire efficacy	149 - 156 lm/W
Max. system power	36 W
Rated luminous flux according to IEC 62722-2- 1	3112 - 5347 lm
Colour of light	White
Colour temperature	4000 - 4000 K

Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, white, 4000K

	BEL11780
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	25 mm
Length	595 mm

Brand	BELL LIGHTING
Art. N°	BEL11780
Sales unit	pc
EAN PCE	501358811780
EAN QTY PCE	1
Intrastat code	94054099