

Luminaires

Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, White, 4000K, Da

BEL11784



Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, White, 4000K, Dali Dim

	BEL11784
Suitable for ceiling mounting	Yes
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	220 - 240 V
With control gear	Yes
Dimmable	Yes
Dimming 0-10 V	Yes
Dimming DALI	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP65
Emergency power supply system	None
Rated ambient temperature according to IEC 62722-2-1	0 - 35 °C
Luminaire efficacy	149 - 149 lm/W
Max. system power	36 W
Rated luminous flux according to IEC 62722-2- 1	5347 - 5347 lm
Colour of light	White
Colour temperature	4000 - 4000 K

Arial Multi Backlit IP65 LED Panel - 25mm 600x600mm, White, 4000K, Da

	BEL11784
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	25 mm
Length	595 mm
Built-in height/depth	25 mm
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BELL LIGHTING
Art. N°	BEL11784
Sales unit	pc
EAN PCE	11784
EAN QTY PCE	1
Intrastat code	39111541