

Luminaires

Aqua Connect LED 4CCT Wattage Switchable Bulkhead

BEL70200



Aqua Connect LED 4CCT Wattage Switchable Bulkhead

	BEL70200
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Material cover	Plastic, opal
Type of grid	Matt
Nominal voltage	220 - 240 V
Nominal current	112 - 112 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), front side	IP65
Impact strength	IK10
Protection class according to IEC 61140	II
Emergency power supply system	Peripheral (individual battery)
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Suitable for emergency lighting	Yes
Emergency function monitoring system	Automatic self test
Luminaire efficacy	120 - 140 lm/W
Max. system power	16 W
Rated luminous flux according to IEC 62722-2- 1	1080 - 2240 lm
Colour of light	White
Colour temperature	3000 - 6000 K
Colour rendering index CRI	80-89
Width	325 mm

Aqua Connect LED 4CCT Wattage Switchable Bulkhead

	BEL70200
Height/depth	75 mm
Outer diameter	325 mm
Colour of light adjustable	Positions

Brand	BELL LIGHTING
Art. N°	BEL70200
Sales unit	pc
EAN PCE	5013588702001
EAN QTY PCE	1
Intrastat code	85392992