

Domestic switching devices

Bidirectional Bluetooth module capable of powering devices such as DMBLINDMAX SO



Bidirectional Bluetooth module capable of powering devices such as solenoid valves, motors, motorized shutters, controlled by 3 wires. App control. - 230V AC + 15%Contact : 5A maxGarantie : 5 ansCo

	DMBLINDMAX
Assembly arrangement	Basic element
Method of operation	Push button
Number of units	1
App control via Bluetooth	Yes
Dimming phase cut-on (leading edge)	No
Dimming phase cut-off (trailing edge)	No
Serial dimmer	No
Type of load	Other
Substation input	Yes
Light value memory	No
Applicable with button	Yes
Applicable with movement sensor	No
Applicable with presence indicator	No
Applicable with time switch/timer	No
Applicable with transmission button	No
Applicable with infrared button	No
Min. brightness controllable	No
Mounting method	Flush-mounted
Type of fastening	Other
Material	Plastic
Material quality	Thermoplastic
Colour	Black
Transparent	No
Suitable for degree of protection (IP)	IP20
Nominal voltage	230 - 230 V
Frequency	50 - 50 Hz
Control voltage	230 - 230 V

Bidirectional Bluetooth module capable of powering devices such as SO

	DMBLINDMAX
Nominal power inductive load	1150 VA
Connection type	Screwed terminal
Device width	46 mm
Device height	48 mm
Device depth	18 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Brand	DOMINTELL
Art. N°	DMBLINDMAX
Sales unit	pc
EAN PCE	5425014390308
EAN QTY PCE	1
EAN QTY C01	10