ERSADUR pairs of desoldering tips, series 422/452

Lead-free Bleifrei SAFE ersa

- DIGITAL 2000 A with CHIP TOOL
- MICRO-CON 60 iA with SMD DESOLDERING PINCETTE 40
- REWORK 80
- SMD 8000
- SMT UNIT 60 AC/A with CHIP TOOL/ SMD DESOLDERING PINCETTE 40
- all i-CON stations with CHIP TOOL

0452FDLF040



4 mm, for e.g. SO 8 GT/14 GT/16GT

0422ED



6 mm, for e.g. SOIC 8

0452EDLF060



6 mm, for e.g. SOIC 8

0452FDLF075



7.5 mm, for e.g. SOIC 2 / SOT 23

0452FDLF100



10 mm, for e.g. SOIC 16

0452FDLF125



12.5 mm, for e.g. SOIC 20

0452FDLF150



15 mm, for e.g. SOIC 24

0452FDLF175



17.5 mm, for e.g. SOIC 28

0452FDLF200



20 mm, for e.g. SOIC 32

0452FDLF250



25 mm, for e.g. SOIC 40

0452FDLF275



27.5 mm, for components of 27.5 mm side length

0452FDLF400



40 mm, for components of 40 mm side length

0452QDLF100



90°, length 10 mm, for e.g. PLCC 20

0452QDLF125



90°, length 12.5 mm, for e.g. PLCC 28

0452QDLF150



90°, length 15 mm, for e. g. QFP, TQFP and TTQFP 80T25

0452QDLF175



90°, length 17.5 mm, for e.g. PLCC 44

0452QDLF200



90°, length 20 mm, for e.g. PLCC 52

0452QDLF250



90°, length 25 mm, for e.g. PLCC 68

0452RDLF150



length 15 x 12.5 mm, for e.g. PLCC 32

0452RDLF225



length 22.5 x 16.5 mm, for e.g. QFP 100

0422MD



ellipse, for MELF and MINI-MELF

0452MDLF020



ellipse, for MELF and MINI-MELF

0422SD



for MICRO-MELF

***Please note:**

Tips 0422SD must be used in combination with the tip turn protection set to ensure good results.

Tip turn protection set for TC 40 desoldering tweezers and DESOLDERING PINCETTE 40 on request.

Hot-air nozzle series 472

Lead-free Bleifrei SAFE ersa

- i-CON VARIO 2 with i-TOOL AIR S hot-air iron
- i-CON VARIO 4 with i-TOOL AIR S hot-air iron

0472AR



hot-air nozzle, 2 mm ø

0472BR



hot-air nozzle, 4 mm ø

0472CR



hot-air nozzle, 6 mm ø

0472DR



hot-air nozzle, bent, 1.7 mm / 0.067 in ø

0472ER



hot-air nozzle, bent, 3.5 mm / 0.138 in ø

Dimensions without pre-tinning