

Equipment for workshop/construction site

GOLIA cable reel Ø 420 mm. trailer-mounted IP55 cable 50 m.
3G2,5 H07

FA12-160



GOLIA cable reel Ø 420 mm. trailer-mounted IP55 cable 50 m. 3G2,5 H07RN-F plug 2P+E 16A 200-250V
6h IP67 3 sockets 2P+E 16A 200-250V 6h IP67 central disc Ø 205 mm. + thermal cut-out

	FA12-160
Housing material	Plastic
Cable assembly	H07RN-F
Core cross section	2.5 mm ²
Number of cores	3
Number of CEE socket outlets (IEC 60309)	3
Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets with protective contact CEE 7/5 (type E)	0
Number of socket outlets British Standard BS 1363	0
Number of socket outlets Italian standard type Bipasso	0
Number of socket outlets Italian standard type P11	0
Number of socket outlets Italian standard type P17	0
Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0
Number of socket outlets Swiss standard type 13	0
Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0
Type of mains connection	CEE for industrial purposes (IEC 60309)
Cable length	50 m
With mounting frame	Yes
Suitable for wall mounting	No
Automatic cable winding	No

GOLIA cable reel Ø 420 mm. trailer-mounted IP55 cable 50 m. 3G2,5 H07

	FA12-160
With thermal overload protection	Yes
With locking	No
With lamp	No
With charging cable for E-Mobility	No
Earthing cable reel	No
Protection	Other
Leakage current type	Other
With personal protection PRCD	No
Degree of protection (IP)	IP55
Colour	Orange

Brand	FANTON
Art. N°	FA12-160
Colour	orange
Sales unit	pc
EAN PCE	8015450121603
EAN QTY PCE	1
Intrastat code	85444290