

# Thin-walled shrink tube in unwinding boxes - Shrink rate 2: 1



## application

- Universally applicable for insulating marking bundling and protecting wires

## properties

- UV-resistant
- Good electrical properties
- Good resistance to chemical influences
- Flame retardant (except transparent)
- Lead and cadmium free
- Temperature range -55°C to + 135 ° C
- Tested to UL224 SAE-AMS-DTL-23053/5
- Class 1 (Colors) Class 2 (transparent)
- MIL-23053 / CSA C 22.22 / DEF-STAN 59-97 Class 3
- Not corrosive

Application ø from - to mm	Shrinkage D ø D mm	Wall thickness W mm	Content m	Article number	Type
1.4 - 0.9	1.6 - 0.8	0.45	15	104 100.	SSB 1.6 - 0.8
1.8 - 1.4	2.4 - 1.2	0.50	15	104 200.	SSB 2.4 - 1.2
2.7 - 1.8	3.2 - 1.6	0.50	15	104 250.	SSB 3.2 - 1.6
3.6 - 2.6	4.8 - 2.4	0.50	10	104 300.	SSB 4.8 - 2.4
5.7 - 3.6	6.4 - 3.2	0.65	10	104 400.	SSB 6.4-3.2
8.5 - 5.7	9.5 - 4.8	0.65	10	104 500.	SSB 9.5 - 4.8
11.4 - 8.5	12.7 - 6.4	0.65	8	104 600.	SSB 12.7 - 6.4
18.0 - 11.4	19.0 - 9.5	0.75	7	104 700.	SSB 19.0 - 9.5
23.0 - 18.0	25.4 - 12.7	0.90	4	104 800.	SSB 25.4 - 12.7
3.6 - 2.6	4.8 - 2.4	0.50	10	104 300. 11	SSB 4.8 - 2.4
5.7 - 3.6	6.4 - 3.2	0.65	10	104 400. 11	SSB 6.4-3.2
8.5 - 5.7	9.5 - 4.8	0.65	10	104 500. 11	SSB 9.5 - 4.8
11.4 - 8.5	12.7 - 6.4	0.65	8	104 600. 11	SSB 12.7 - 6.4
18.0 - 11.4	19.0 - 9.5	0.75	7	104 700. 11	SSB 19.0 - 9.5
23.0 - 18.0	25.4 - 12.7	0.90	4	104 800. 11	SSB 25.4 - 12.7

Specify color key as an addition to the article number:

black = .1 - blue = .2 - red = .4 - grey = 8 - brown = .9 - green/yellow = .11 - transparent = .12