

## Thin-walled shrink tube with SUM glue



### application

- Universally applicable for insulating and bundling of wires

### properties

- UV-resistant
- Temperature range: - 45 to +125 ° C
- flame retardant
- Color: Black
- Good resistance to many chemicals
- Rolls can contain part lengths
- Not corrosive

#### Thin-walled shrink tubing with adhesive type SUM - Shrink Ratio 3: 1

Application ø from - to mm	Shrinkage D ø D * mm	Wall thickness W * mm	Length m	Article number	Type
2 - 1	3 - 1	1.0	1	105 900.1C	SUM 3 - 1/1000
4 - 2	6 - 2	1.0	1	105 901.1C	SUM 6 - 2/1000
7 - 3	9 - 3	1.4	1	105 902.1C	SUM 9 - 3/1000
9 - 4	12 - 4	1.8	1	105 903.1C	SUM 12 - 4/1000
16 - 7	19 - 6	2.3	1	105 904.1C	SUM 19 - 6/1000
21 - 9	24 - 8	2.5	1	105 905.1C	SUM 24 - 8/1000
28 - 9	32 - 8	2.5	1	105 925.1C	SUM 32 - 8/1000
36 - 14	40 - 13	2.5	1	105 906.1C	SUM 40 - 13/1000

.1C = 20 pieces à 1 m in presentation box