

Thick-walled shrinkable tube with adhesive



application

- Universal application for insulating and sealing

properties

- UV-resistant
- Halogen free
- Temperature range: - 40 to + 135 ° C
- Color: Black
- Standard length 1000 mm
- Very good adhesion to PVC, PE, Cu, Al, Pb
- Good resistance to many chemicals
- Very good electrical properties
- Not corrosive

Thick walled shrink tubing coated with adhesive - type SK 5

Application ø from - to mm	Shrinkage D ø D * mm	Wall thickness W * mm	Article number	Type
10 - 3	12 - 3	2.5	120 000	SK 5 12 - 3/1000
19 - 6	20 - 6	2.7	120 100	SK 5 20 - 6/1000
26 - 8	30 - 8	4.0	120 200	SK 5 30 - 8/1000
36 - 13	40 - 13	4.0	120 300	SK 5 40 - 13/1000
50 - 18	55 - 18	4.1	120 400	SK 5 55 - 18/1000
65 - 20	69 - 20	4.1	120 500	SK 5 69 - 20/1000
88 - 30	92 - 26	4.1	120 600	SK 5 92 - 26/1000
110 - 37	117 - 37	4.1	120 700	SK 5 117 - 37/1000
135 - 30	140 - 50	4.1	120 702	SK 5 140 - 50/1000
158 - 55	165 - 65	4.1	120 703	SK 5 165 - 65/1000