

4- to 5-core connection sleeves for plastic cables suitable for compression connectors, tested in accordance with DIN EN 50393

application



- Outdoors and in the ground, in water and cable ducts, indoors
- For connecting plastic cables with insulation made of PVC, PE and PU without reinforcement
- Suitable for compression connectors for aluminum and copper cables

properties

- Halogen free
- UV-resistant
- Resistant to environmental influences, alkaline earths and chemical influences
- Crosslinked polyolefin hoses coated with hot melt adhesive
- Unlimited storage
- Cross Waterproof
- Good electrical insulation values

4- to 5-core connection sleeves for plastic cables suitable for compression connectors

N (A) YY, N (A) 2Y (2) Y, N (A) 2X (2) Y Number of cores, cross section mm ²	Connector ø max. mm	Article number	Type
5 x 1.5 - 6	10	500 100	SM 5 1.5 - 6
5 x 1.5 - 16	10	500 200	SM 5 1.5 - 16
5 x 16 - 25	18	500 300	SM 5 16 - 25
4 x 6 - 25	18	500 400	SM 4 6 - 25
4 x 16 - 50	18	500 500	SM 4 16 - 50
4 x 25 - 95	26	500 600	SM 4 25 - 95
4 x 35 - 150	28	500 700	SM 4 35 - 150
4 x 70 - 150	38	500 800	SM 4 70 - 150
4 x 95 - 300	38	500 900	SM 4 95-300