

repair sleeve



application

- Outdoors and in the ground, in water and cable ducts, indoors
- For safe repair of cable sheath damage to low and medium voltage cables
- Requirements for cable sheath tests according to VDE 0298 part 1 are fulfilled

properties

- UV-resistant
- Halogen free
- High tensile strength
- Internal pressure tight to 0.15 Mpa

Repair sleeves for paper and plastic insulated cables

Recommended application range ø min. mm	Recommended application range ø max. mm	Article number	Type
10	30	714 250	RM 30 - 10/250
10	30	714 500	RM 30 - 10/500
10	30	714 750	RM 30 - 10/750
10	30	714 1000	RM 30-10 / 1000
13	47	715 250	RM 47- 13/250
13	47	715 500	RM 47 - 13/500
13	47	715 750	RM 47 - 13/750
13	47	715 1000	RM 47-13 / 1000
20	77	725 250	RM 77 - 20/250
20	77	725 500	RM 77 - 20/500
20	77	725 750	RM 77 - 20/750
20	77	725 1000	RM 77-20 / 1000
30	100	730 250	RM 100-30/250
30	100	730 500	RM 100-30/500
36	140	735 250	RM140-36/250
36	140	735 500	RM 140-36/500
55	185	736 500	RM185-55/1000