

## FILOseal+HD FIRE

FiloSeal+HD FIRE provides a strong support system using our specially formulated material called Formite which builds up like a honeycomb structure. FiloSeal+HD FIRE is suitable for sealing any cable configuration or pipes contained in one duct and also allows easy re-entry of the seal to add or remove cables or pipes as required.

The Filoform duct sealing system FiloSeal+HD FIRE uses our MD+ sealant which is easily applied from a skeleton gun. The high quality, one component, flexible sealant "MD+" is based on a silicon compound that cures with air (Humidity).

The unique design of the hexagonal tubes makes positioning and separation of the cables very simple while also providing a strong backing for the MD+ to be applied on.

- Up to 4 hours fire resistance in transit frames (single side)
- Up to 4 hours fire resistance in ducts
- Tested to BS EN1366-3 2009
- Up to 2 bar Pressure Resistance
- 100Kg pulling Force on the cables when sealed
- 10xd at 45°, with 1 bar pressure bending test

## **FEATURES**

- High levels of Gas and Water tightness
- Excellent adhesion, applicable to all common building materials
- Shows fire resistance properties
- Resistant against Water, Alkaline, Chemical agents
- Resistant to Hydrogen Sulphide / Methane and many other Gases (NedLab)
- Non corrosive
- Solvent free
- Shock absorbing
- Non toxic, neutral and almost odourless
- Complies with ATEX regulations
- Suitable for any shaped duct / bore hole / opening
- · Quick and easy installation
- A complete kit
- Seals all known materials, PVC & PE sheathed cables, PILC, (HD) PE pipes
- Suitable for renovations, can be installed retrospectively
- Resistant to Rats
- Resistant to termites (Mastotermes
- Darwiniensis) Northern Australian termites

Product Name	Duct diameter minmax. (mm)	Order unit
FiloSeal+HD FIRE - 75 mm > 110 mm	Ø 110 max.	per piece
FiloSeal+HD FIRE - 125 mm > 160 mm	Ø 160 max.	per piece
FiloSeal+HD FIRE - 180 mm	Ø 180 max.	per piece
FiloSeal+HD FIRE - 200 mm	Ø 200 max.	per piece
FiloSeal+HD FIRE - 225 mm	Ø 225 max.	per piece
FiloSeal+HD FIRE - 250 mm	Ø 250 max.	per piece

Watch the FiloSeal+HD productvideo online on our website.