

Sealing Caps

Filoform sealing caps have been developed to provide an effective and simple solution to all splash water and dirttight sealing requirements in HDPE ducts and protective sleeves.

The sealing caps are standard dirt and splash watertight. After mounting with sealing compound Filoform Fill & Seal (art.nr. 80840) or Fire & Water-seal (art.nr. 80845) the Filoform sealing plugs easily exceed the specifications of NEN 2768.

The Filoform sealing caps are made from a high quality TPE, this material has a hardness of 40 Shore A.



Item number	Description	Outside diameter HDPE duct (mm)	Maximum cable / pipe diameter in the duct (mm)	Order unit
822617	Sealing cap 16/2x4mm type16	16	2x4mm	10 pcs/carton
822410	Sealing cap 40/10x7mm(type7)	40	10x7mm	40 pcs/carton
822613	Sealing cap 40/5x10mm(type13)	40	5x10mm	40 pcs/carton
822615	Sealing cap 40/4x10-12 type14	40	4x10-12mm	10 pcs/carton
822616	Sealing cap flexb. 40 type15	40	closed end cap	25 pcs/carton
822507	Sealing cap 50/7x10mm(type10)	50	7x10mm	25 pcs/carton
822510	Sealing cap 50/5x12mm+2x12mm	50	5x12mm + 2x12mm	25 pcs/carton
822514	Sealing cap 50/14x7mm(type11)	50	14x7mm	25 pcs/carton

Universal HDPE sealing plugs

Filoform sealing plugs have been developed to provide an effective and simple solution to all splash water and dirttight sealing requirements in HDPE ducts, protective sleeves and diamond-drilled ducts.

The sealing plugs are formed from one part, with a seam part. Due to this unique construction, the plug can be used as blind and sealing plug.

Furthermore, the sealing plug is inside specially shaped. This special shape enables you to adapt the plug easily to the diameter of the cable or subduct. This enables you to obtain savings in inventory costs since only a very limited number of types of plugs are needed.

The Filoform sealing plug is directly applicable in situations where a blind plug temporarily without cable or subduct inside the HDPE duct should be sealed or to seal openings for future transit extensions are provided.

To apply the sealing plug, the plug can be adjusted to the correct cable or subduct diameter by shortening the plug using the size chart on the packaging.

The sealing plugs are standard dirt and splash watertight. After mounting with sealing compound Filoform Fill & Seal (art.nr. 80840) or Fire & Water-seal (art.nr. 80845) the Filoform sealing plugs easily exceed the specifications of NEN 2768.

The Filoform sealing plugs are made from a high quality TPE, this material has a hardness of 40 Shore A.



Item number	Description	Outside diameter HDPE duct (mm)	Maximum duct diameter (mm)	Maximum cable / pipe diameter in the duct (mm)	Order unit
82212	Sealingplug HDPE 32mm	32	27,0 - 28,5	6,0-16,0	40 pcs/carton
82217	Sealingplug HDPE 40mm HW	40	31,5 - 33,0	5,0-22,0	40 pcs/carton
82214	Sealingplug HDPE 40mm TW	40	34,4 - 36,0	6,0-22,0	30 pcs/carton
82215	Sealingplug HDPE 50mm	50	39,5 - 41,5	8,0-20,0	10 pcs/carton