


RQK**Connectors**

Plastic coupler for rational tubing assembly by just putting on

Temperature: -40°C ... +120°C

Material: TPE plastics

IP class [acc. to EN 60529]: IP 66

**APPLICATIONS:**

- Application: machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



FLEXA No.	Colour	OD [mm]	Ø B1 [mm]	Ø B2 [mm]	D [mm]	Weight [kg/100]	PU [pcs.]
15020066210	Black	OD1 - 10,0 / OD2 - 10,0	17,5	17,5	33,5	0,300	10
15020066207	Black	OD1 - 13,0 / OD2 - 13,0	20,0	20,0	36,5	0,370	10
15020066208	Black	OD1 - 15,8 / OD2 - 15,8	23,0	23,0	44,5	0,500	10
15020066209	Black	OD1 - 18,5 / OD2 - 18,5	26,5	26,5	48,0	0,800	10
15020066201	Black	2 x OD 21,2	29,5	29,5	46,0	0,800	10
15020066202	Black	OD1 - 28,5 / OD2 - 28,5	36,5	36,5	46,0	1,100	10
15020066203	Black	OD1 - 34,5 / OD2 - 34,5	45,0	45,0	48,0	2,000	10
15020066204	Black	OD1 - 42,5 / OD2 - 42,5	55,0	55,0	60,0	4,000	10
15020066205	Black	OD1 - 54,5 / OD2 - 54,5	67,5	67,5	70,0	6,100	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.