

Protective hose systems

ROHRFLEX-PA PA6 gris (AD13,0)

0233201010



ROHRflex PA 6. Flexible corrugated tubing, fine profile.

	0233201010
Nominal diameter	13 mm
Nominal size in inch	5/16 inch
Material	Polyamide (PA)
Compressive strength	125 N
Operating temperature	-40 - 120 °C
Bending radius, static	20 mm
Bending radius, dynamic	45 mm
Oil resistant	Yes
Colour	Grey
Sheathing material	Not sheathed
Flame accelerating	No
Bending strength	Flexible
Tensile strength	100 N
Lengthwise slotted	No
Closable (two-part)	No
Halogen free	Yes
With draw wire	No
High conducting inner coating	No
Fire resistance according to UL94	V0
Inner diameter	10 mm
Approved according to DIN EN 61386-23	Yes
Approved according to LUL/British Standard	Yes
Approved according to Lloyd's Register TA	Yes
Outer diameter	13 mm
Approved according to UTAC	No

ROHRFLEX-PA PA6 gris (AD13,0)

	0233201010
Approved according to DIN 5510	Yes
Approved according to VdTÜV/GGVSEB	Yes
Brand	FLEXA
Art. N°	0233201010
Sales unit	m
EAN PCE	4025113105318
EAN QTY PCE	1
Intrastat code	85365011