

Protective hose systems

LI-M. Connecteur en métal- droit- filetage extérieur- douille fixe- o 5010012016



LI-M. Metal connector, straight, external thread, fixed socket, rotatable. - nickel-plated brass - polished brass tip - spring steel circlip - M 16 x 1,5 Ø 17 - IP40 -

	5010012016
Nominal diameter	17 mm
Nominal size in inch	3/8 inch
Model	Straight
Revolving thread	No
Construction type	External thread
Connection type to housing	Thread
Thread type	Metric
Thread connection size	M16 x 1.5
Thread per inch	1.5
One-piece	No
Housing material	Brass
Surface protection	Nickel-plated
Lowest inner diameter hose	13 mm
Max. outer diameter hose	17 mm
Thread length	10 mm
Total length	33 mm
Total height	25 mm
Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit CSA	No
Approved in combination with protective conduit UL	No
Approved in combination with protective conduit FI	No
Operating temperature	-40 - 250 °C
Number of inlets	1
With earthing connection	No

LI-M. Connecteur en métal- droit- filetage extérieur- douille fixe- o

Brand	FLEXA
Art. N°	5010012016
Sales unit	pc
EAN PCE	4025113143372
EAN QTY PCE	1
Intrastat code	74122000