

Protective hose systems

RQG-M. Raccord en plastique- type rapide- droit- filetage extérieur 5020065009



RQG-M. Plastic connector, quick-type, straight, outer thread, high-density.

	5020065009
Nominal diameter	21.2 mm
Nominal size in inch	1/2 inch
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	No
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Thread connection size	M25 x 1.5
Thread per inch	1.5
Thread material	Polyamide (PA)
Thread length	13 mm
Total length	44.5 mm
Total height	29.5 mm
Material	Polyamide (PA)
Material sealing	Thermoplastic elastomer (TPE)
Lowest inner diameter hose	16.5 mm
Max. outer diameter hose	21.2 mm
Colour	Grey
Approved in combination with protective conduit CSA	Yes
Approved in combination with protective conduit UR	Yes
Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit Lloyd's Register	Yes
Operating temperature	-40 - 120 °C

RQG-M. Raccord en plastique- type rapide- droit- filetage extérieur h

	5020065009
Approved in combination with protective conduit VdTÜV/GGVSEB	Yes

Brand	FLEXA
Art. N°	5020065009
Sales unit	pc
EAN PCE	4025113189806
EAN QTY PCE	1
Intrastat code	39174000