

Protective hose systems

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

5111028225



RQGKZE-M. Plastic connector, quick-type, straight, nickel-plated brass outer thread, strain relief and shielding, high-density.

	5111028225
Nominal diameter	28.5 mm
Nominal size in inch	3/4 inch
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	No
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Thread connection size	M25 x 1.5
Thread per inch	1.5
Thread material	Brass
Thread length	7 mm
Total length	71 mm
Material	Polyamide (PA)
Material sealing	Thermoplastic elastomer (TPE)
Lowest inner diameter hose	16 mm
Max. outer diameter hose	42.8 mm
Colour	Black
Approved in combination with protective conduit CSA	Yes
Approved in combination with protective conduit UR	Yes
Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit Lloyd's Register	Yes
Operating temperature	-50 - 120 °C

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

	5111028225
Approved in combination with protective conduit VdTÜV/GGVSEB	No

Brand	FLEXA
Art. N°	5111028225
Sales unit	pc
EAN PCE	4025113196217
EAN QTY PCE	1
Intrastat code	39174000