

RQGR

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick type, reducer, high density, EN 45545-2 (HL3)


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 68 | IP 69K

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



APPLICATIONS:

- Application: for static and dynamic applications indoor and outdoor of railway cars / heavy machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



FLEXA No.	Colour	OD [mm]	Ø B [mm]	Ø I [mm]	D [mm]	Weight [kg/100]	PU [pcs.]
15601010221	Black	OD1 10,0, OD2 21,2	17,0	8,0	58,0	0,800	10
15601010228	Black	OD1 10,0, OD2 28,5	17,0	7,0	63,0	1,600	10
15601013215	Black	OD1 13,0, OD2 15,8	20,0	10,0	56,0	0,900	10
15601013221	Black	OD1 13,0, OD2 21,2	20,0	10,0	60,5	0,900	10
15601013228	Black		20,0	10,0	62,5	1,500	10
15601015221	Black	OD1 15,8, OD2 21,2	23,0	14,0	60,5	1,200	10
15601015228	Black	OD1 15,8, OD2 28,5	23,0	12,5	63,0	1,600	10
15601015234	Black	OD1 15,8, OD2 34,5	23,0	13,5	60,0	1,700	10
15601021228	Black	OD1 21,2, OD2 28,5	29,5	17,0	65,0	2,140	10
15601021234	Black	OD1 21,2, OD2 34,5	29,5	17,0	64,0	2,000	10
15601021242	Black	OD1 21,2, OD2 42,5	29,5	17,0	70,5	3,600	10
15601021254	Black	OD1 21,2, OD2 54,5	29,5	17,0	86,0	4,000	5
15601028234	Black	OD1 28,5, OD2 34,5	37,0	23,5	70,0	3,200	10
15601028242	Black	OD1 28,5, OD2 42,5	37,0	23,5	78,0	3,700	10
15601028254	Black	OD1 28,5, OD2 54,5	37,0	23,5	81,5	4,200	5
15601034242	Black	OD1 34,5, OD2 42,5	44,0	30,0	75,0	3,800	10
15601034254	Black	OD1 34,5, OD2 54,5	44,0	30,0	83,0	4,400	5
15601042254	Black	OD1 42,5, OD2 54,5	52,0	39,0	84,0	4,500	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.