

Pipe inspection camera system „BRlcamL“

Video inspection system for visual inspection of pipes, hollow bodies and spaces as well as finding blockages or damage!

Pipe inspection camera system BRlcamL with a swivelling camera head, only 28 mm diameter and 40 m fiberglass cable, intelligent compact design combined with simple operation and easy transportation, thanks to the aluminium frame.

This waterproof system is complete with transmitter module can be used between and can be detected, tracked and located by locating devices, operating at 512 Hz. The camera head of the BRlcamL can be rotated 360° and swiveled by 210° and enables an exact Driving through connections and checking pipe branches.

The display unit is surrounded by a robust, waterproof and airtight plastic case and can be used in cramped working conditions or for better transport of the separated push cable unit.

On the 10" TFT monitor with a Resolution of 800 x 600 pixels the smallest Defects will be recognized and the number of meters inserted are shown. The BRlcamL is equipped with a multifunctional Control panel with QWERTY keyboard for entering text, as also an integrated microphone for voice recording during video recording on SD card or USB stick. This intelligent system even has a device for cleaning the fibre cable after use by pushing it back, which removes adhering water and impurities. These are collected in the waterproof body, which can then be emptied outdoors.

By unscrewing the transmitter unit and inserting an optional adapter, bends from DN50 upwards are possible. This system can also be operated with a 10 or 20 meter long hand reel with a Ø 12 mm camera head.

Content:

- 360°/210° rotating/swivelling camera head Ø 28 mm
- Camera cable: Ø 7mm/40 metres long
- Steel coil, Meter counter
- 6-pin camera connection
- Cleaning brush
- 512 Hz sender
- IP68 Multifunctional control device in the IP66 case, 10" TFT monitor with USB/SD recording
- Text and voice input using the QWERTZ keyboard
- Control buttons for swivelling camera head
- Operated with 6600 mAh Li-Ion battery or current
- Mains adapter, Guide ball and star for camera head
- Video cable 1 metres 6-pin, Remote operation



Ø 28 mm	 Ø 7 mm ← 40 m →	DN70 DN160	 360° 210°
10" TFT	↑ 800 x 600 Px ↓	Akku Li-Ion 6600 mAh	 IP68



Art. no.	Camera head Ø mm	Cable ↔ m	kg	PU
3741	28	40	17,080	1