

T-Handle socket wrenches 1000 V

chrome vanadium steel, full insulated, for hexagon nuts, DIN 7440, 2-coloured coating-insulation - inside yellow/outside red

⚠ 1000 V IEC 60900:2004



Art. no.	WS	BL	handle	kg	PU
110000	10	200	160	0,300	1
110002	11	200	160	0,315	1
110004	12	200	160	0,320	1
110006	13	200	160	0,320	1
110008	14	200	160	0,426	1
110010	17	200	160	0,401	1
110012	19	200	160	0,430	1
110022	11	300	160	0,429	1
110024	12	300	160	0,375	1
110026	13	300	160	0,380	1
110028	14	300	160	0,385	1
110030	17	300	160	0,534	1
110032	19	300	160	0,556	1
110034	22	300	160	0,662	1
110036	24	300	160	0,990	1

Cross type socket wrenches 1000 V

chrome vanadium steel, no contact with steel insert, full insulated, 2-coloured coating-insulation - inside yellow/outside red

⚠ 1000 V IEC 60900:2004



Art. no.	WS	BL	kg	PU
110070	10-11-14-17	200	0,451	1
110074	11-12-13-17	200	0,225	1
110076	10-13-14-17	200	0,455	1
110078	11-13-14-17	200	0,449	1
110080	13-17-19-22	200	0,502	1

Counter hold spanners 1000 V

chrome vanadium steel (31 CrV 3), 2-coloured coating-insulation - inside yellow/outside red

⚠ 1000 V IEC 60900:2004



Art. no.	WS	TL	kg	PU
110081	10	200	0,118	1
110083	12	200	0,120	1
110084	13	200	0,140	1
110085	14	250	0,150	1
110087	16	260	0,249	1
110089	17	270	0,255	1
110091	18	265	0,250	1
110093	19	270	0,275	1
110095	20	275	0,300	1
110097	22	275	0,300	1
110099	24	270	0,350	1

Right angle allen keys 1000 V

chrome vanadium steel, for hexagon socket screws, full insulated, 2-coloured coating-insulation - inside yellow/outside red

⚠ 1000 V IEC 60900:2004



Art. no.	WS	kg	PU
110042	3	0,016	1
110044	4	0,029	1
110046	5	0,045	1
110048	6	0,051	1
110050	8	0,103	1
110052	10	0,220	1
110054	12	0,352	1

T-handle allen keys 1000 V

chrome vanadium steel, for screws with hexagon inserts, full insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2012



Art. no.	WS	kg	PU
110060	5	0,222	1
110062	6	0,227	1
110064	8	0,224	1

Single ended spanners 1000 V

chrome vanadium steel, full insulated, offset at 15°, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2012



Art. no.	WS	TL	strength	kg	PU
110260	6	75	3	0,021	1
110262	7	80	3,5	0,020	1
110264	8	85	3,5	0,032	1
110266	9	100	4	0,035	1
110268	10	120	5	0,035	1
110270	11	130	5,5	0,044	1
110272	12	140	5,5	0,064	1
110274	13	155	6	0,061	1
110276	14	170	6	0,084	1
110278	17	185	6,5	0,121	1
110280	19	210	7,5	0,140	1
110282	22	230	8,5	0,215	1
110284	24	250	9,5	0,242	1
110286	27	290	11,5	0,338	1
110288	30	345	13	0,390	1
110290	32	350	15	0,503	1