

## Electrical installation, isolation and connection materia

### 95mm<sup>2</sup> CRIMP SLEEVE

291534

**haupa**®

### 95mm<sup>2</sup> CRIMP SLEEVE

|                                            | 291534                  |
|--------------------------------------------|-------------------------|
| Nominal cross section                      | 95 - 95 mm <sup>2</sup> |
| Model                                      | DIN-version             |
| Sleeve form                                | Long                    |
| Suitable for solid conductors              | No                      |
| Suitable for stranded conductors           | Yes                     |
| Suitable for fine strand conductors        | No                      |
| Suitable for high temperatures (to 650 °C) | No                      |
| Suitable for insulated varnish             | No                      |
| Suitable for round conductors              | Yes                     |
| Suitable for flat conductors               | No                      |
| Material                                   | Copper                  |
| Insulation                                 | None                    |
| Voltage level                              | Up to 10 kV             |
| Type of connection                         | Percussion connector    |
| Number of branches                         | 2                       |
| For pull protected connections             | No                      |
| Oil stop/centre bar                        | No                      |

|                |               |
|----------------|---------------|
| Brand          | HAUPA         |
| Art. N°        | 291534        |
| Sales unit     | pc            |
| EAN PCE        | HUUU000000762 |
| EAN QTY PCE    | 1             |
| EAN C01        | 4011923100957 |
| EAN QTY C01    | 15            |
| Intrastat code | 94054910      |