





Art.No. 267252

HUPshrink21TW thin-walled 2:1


Art.No.	267252
EAN	4011923590505
Model	Thin-walled
Shrink rate	2:1
With inner glue	No
Inner diameter before heat-shrink	1.6 mm
Inner diameter after heat-shrink	0.8 mm
Wall thickness after shrinking	0.33 mm
Colour	Black
Material	Polyolefin (PO-X)
Operation temperature	-55 - 125 °C
Length	1.2 m
Halogen free	Yes
VPE	1

Radiation cross-linked polyolefin, self extinguishing according to MV SS 302, flexible, universally applicable, Dielectric strength: 15 - 25 KV/mm according to DIN 53481, shrinking temperature > 70° C, continuous operating temperature - 55° C to 125° C, packaged in a polybag, thin-walled



Distributed by:

HAUPA GmbH, Lange Straße 40, 42857 Remscheid, Germany, Tel. +49 (0)2191 8418-0, info@haupa.com
 HAUPA Ibérica S.L.U., C/ Muralla de Sant Llorenç, 37 2ª, 08302 Mataró (Barcelona), Spain, Tel. +34 93-63-82-111
 HAUPA Polska Sp. z o.o., ul. Norwida 11, 55-100 Trzebnica, Poland, Tel. +48 (0)71 387 48 13
 iCON by HAUPA d.o.o., Miše Dimitrijevića 44, 21000 Novi Sad, Serbia, Tel. +381 21 300-2937