

# Special cable cutters

## Universal cable cutter with eccentric drive

- one-hand universal- and steel rope cutter with exchangeable cutting segments
- in the case of wear or changing requirements only the cutting segment need to be replaced
- Cleaner included
- double needle bearing excenter lever 14mm
- very easy to use through reduction of the attrition of the joint
- strong reduction of the manual force
- Lever joint bolt strength 9mm
- central lubrication
- Cone fitting in the bolt with cross drilling on the bearing points
- adjustable level of the transport plugs
- opening of the cutter possible at any time, also suitable for the highest demands without additives

### Separable materials:

- Cable AL /Cu
- Cable with soft steel cover
- Steel covered ropes
- Steel armoured ropes
- Niro ropes
- Flexible steel ropes
- Tracking rope cable
- Steel armoured hose
- ACSR DIN 48 204
- Constructional steel 235JR+AR
- Screws

### Complete set:

- Universal cable cutter
- 1 pair of cutting segments S1 (art. 200178/S1)
- ACSR



Art. no.	TL	mm <sup>2</sup>	fine wiring mm <sup>2</sup>	kg	PU
200178	230	300	240	1,140	1

## Further accessories for cable cutter item no. 200178



**Application:** AL/CU: Cross-section 300 mm<sup>2</sup>, Ø 50 mm  
Flexible steel cables: Cross-section 95 mm<sup>2</sup>, Ø 14 mm  
Niro cables Ø 8 mm, 19/1  
ACSR DIN 48 204: Cross-section 150/25 mm<sup>2</sup>, Ø 20 mm, 7/2.1 mm  
Steel armoured tubing: Ø 50 mm

Art. no.	mm <sup>2</sup>	kg	PU
200178/S1	300	0,100	1



**Application:** AL/CU: Cross-section 150 mm, Ø 30 mm  
Flexible steel cables: Cross-section 70 mm, Ø 12 mm  
Supporting cable: Cross-section 70/300 mm<sup>2</sup>, Ø 12/30 mm, Type 8  
ACSR DIN 48 204: Cross-section 70/12 mm<sup>2</sup>, Ø 11.7 mm, 7/1.44 mm

Art. no.	mm <sup>2</sup>	kg	PU
200178/B	150	0,100	1



**Application:** AL/CU: Cross-section: 350 mm, Ø 50 mm  
Clean cut and low handgrip with large cross sections  
suitable for highly flexible conductors  
not for steel

Art. no.	mm <sup>2</sup>	kg	PU
200178/C	350	0,100	1



**Application:** AL/CU: Cross-section 350 mm, Ø 50 mm  
Flexible steel cables: Cross-section 95 mm<sup>2</sup>, Ø 16 mm  
Cable with soft steel sleeve: Cross-section 240 mm<sup>2</sup>, Ø 50 mm  
Clean cut and normal handgrip

Art. no.	mm <sup>2</sup>	kg	PU
200178/S	350	0,100	1



**Application:** AL/CU: Cross-section 200 mm<sup>2</sup>, Ø 50 mm  
Flexible steel cables: Cross-section 95 mm<sup>2</sup>, Ø 14 mm  
Niro cables: Ø 8 mm, 19/1  
ACSR DIN 48 204: Cross-section 300/50 mm<sup>2</sup>, Ø 24.5, 7/3 mm  
Steel armoured tubing: Ø 50 mm  
Construction steel 235JR+AR: Ø 10 mm, full material  
Screws: Ø 8 mm, 8.8  
Can lead to crimping of steel cables are highly flexible, slightly edgy  
cutaway section, increased handgrip

Art. no.	mm <sup>2</sup>	kg	PU
200178/S2	200	0,100	1

