

COD. 41713

KLIK KLAKE MINI BINARIO MAGNETICO



CEILING



GENERAL

Finishing: Nero / Black

DIMENSIONS

Size 1mt
Weight 1,14 Kg



Accessories



41764


KLIK_KLAK MICRO MASCHERA
COPERTURA 1MT PER RASATURA

41751

Angolo 90° esterno e accessori/ Outer 90°
corner with accessories

41759

KLIK_KLAK MICRO conduttore elettrico




41761

Staffe attacco soffitto kit 2pz / Brackets for
ceiling installation 2 pcs

41132/A

Sospensione con cavo alimentazione 2mt (1
pz) / Suspension 2mt with electrical wire (1 pc)



41753

Giunto a ÓXÓ/ÓXÓ connector



41765

Testata per alimentazione 24V/Front feed 24V



41784

Testata c/ driver 60W 230V dimm./Front feed
w/ driver 60W 230V dimm.



41747

Angolo 90° con spinotti e accessori/ 90° corner
with accessories



41749

Angolo 90° interno e accessori/ Inner 90°
corner with accessories



41763

Kit staffe incasso (2 pz) / Brackets for recessed
installation (2 pcs)




41132

Sospensione 2mt (1 pz) / Suspension 2mt (1
pc)




41757

Staffa connessione (1 pz) / Linear connection
plate (1 pc)




41755

Giunto a ÓTÓ/ÓTÓ connector



41780

Ponte di giunzione elettrica 107mm
H.43mm/Electric bridge connector 107mm
H.43mm



41785

Testata c/ driver 100W 230V dimm./Front feed
w/ driver 10W 230V dimm.



41786

Testata c/ driver 150W 230V dimm./Front feed w/ driver 150W 230V dimm.



42817

Centrale c/ driver 60W 230V dimm./Central feed w/ driver 60W 230V dimm.



42818

Centrale c/ driver 100W 230V dimm./Central feed w/ driver 10W 230V dimm.



42819

Centrale c/ driver 150W 230V dimm./Central feed w/ driver 150W 230V dimm.