

DICROLED TRP DIMMERABILE



Logistic Data

Code	21464
Product	DICROLED TRP DIMMERABILE
Box quantity (pcs.)	10/100
EAN Box	8012878214641
Gross weight of box in kg	7.55
Weight of single lamp in kg	0.075
Length of box in m	0.625
Width of box in m	0.305
Height of box in m	0.21
ETIM class name	LED lamp
Beam angle	60°
Brand of LED	EPISTAR
Power Factor	>0.5
Voltage	220-240

Light Application Parameters

Luminous flux	650 lm
Luminous efficiency of lamp	86.66 lm/W
Colour temperature	2700 K
Colour rendering index Ra	≥80
LLMF at the end of nominal life	0.85(15000h)
SDCM	0.7
Imax(cd)	507.1
Switching cycles	20000


Specification

dimnable	YES
Energylabel from 2013	A+
Suitable for indoors	Yes
Application	general
Base	GUI10
Lamp shape	PAR16


Electrical Parameters

Lamp nominal wattage	7W
Rated wattage	7.5 W
Nominal current (mA)	63 mA
Energy Consumption kWh/1000h	7



Colour Temperature consistency
(SDCM according to Mac Adam's ellipse)



Peak of light intensity (max. cd)



Spectral distribution of the lamp (range 180-800nm)



Dimmerabile

