


ECO OLIVALED ECO

A+



5W EPISTAR	SDCM 1.5	CRI >80	PF >0,4	INSTANT	RoHS
15000h LLMF 0.83	LSP 15000h 0.93	20000	Hg	GARANZIA ANNI 2	LONG LIFE 20000



OLIVALED ECO


codice code	W W	W W	V V	attacco base	colore colour	lumen lumen	fascio beam	imballo packing
21282	5	38(ERP)	220-240	E14	3000°K	450	240°	10/100
21283	5	39(ERP)	220-240	E14	4000°K	460	240°	10/100
21284	5	40(ERP)	220-240	E14	6000°K	470	240°	10/100

ECO COLPO DI VENTOLED

A+



5W EPISTAR	SDCM 1.5	CRI >80	PF >0,4	INSTANT	RoHS
15000h LLMF 0.83	LSP 15000h 0.93	20000	Hg	GARANZIA ANNI 2	LONG LIFE 20000



OLIVALED ECO

codice code	W W	W W	V V	attacco base	colore colour	lumen lumen	fascio beam	imballo packing
21657	5	37(ERP)	220-240	E14	3000°K	430	240°	10/100
21658	5	37(ERP)	220-240	E14	4000°K	440	240°	10/100
21659	5	38(ERP)	220-240	E14	6000°K	450	240°	10/100