


PRO PAR20LED EVO

A+




PAR20LED EVO

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21106	6	57(ERP)	220-240	E27	3000°K	420	410	25°	10/50

PRO PAR38LED EVO

A+




PAR38LED EVO

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21074	15	135(ERP)	220-240	E27	3000°K	1200	1160	30°	5/30



PRO PAR30LED EVO

A+





PAR30LED EVO

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21107	10	80(ERP)	220-240	E27	3000°K	700	680	30°	10/40



PRO AR70LED

A+



AR70LED

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21431	7	67(ERP)	12AC/DC	BA15d	2700°K	490	480	24°	10/100