




ECO DECO-COB-5 38

A+



5W EPISTAR
SDCM 6
CRI >80
PF >0,4
INSTANT
No Infrarad
UV STOP
RoHS
CE
L

LMF 0.83
LSP 15000h
20000
Hg
2 ANNI
LONG LIFE 20000



DECO-COB-5 38

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21137	5	51(ERP)	220-240	GU10	3000°K	400	360	38°	10/200
21138	5	53(ERP)	220-240	GU10	4000°K	420	370	38°	10/200



ECO PAR30LED

A+



10W San'an
SDCM 6
CRI >80
PF >0,5
INSTANT
No Infrarad
UV STOP
RoHS
CE
L

LMF 0.83
LSP 15000h
20000
Hg
2 ANNI
LONG LIFE 20000



PAR30LED TUTTO VETRO

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21353	10	91(ERP)	220-240	E27	3000°K	800	780	50°	1/20



ECO DECO-SMD-5

A+



5W EPISTAR
SDCM 6
CRI >80
PF >0,4
INSTANT
No Infrarad
UV STOP
RoHS
CE
L

LMF 0.83
LSP 15000h
20000
Hg
2 ANNI
LONG LIFE 20000




DECO-SMD-5

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21527	5	63(ERP)	220-240	GU10	3000°K	470	460	48°	10/100
21528	5	66(ERP)	220-240	GU10	4000°K	480	470	48°	10/100


ECO ECO-PIATTADECO

A+



7W EPISTAR
SDCM 6
CRI >80
PF >0,5
INSTANT
No Infrarad
UV STOP
RoHS
CE
L

LMF 0.83
LSP 15000h
20000
Hg
2 ANNI
LONG LIFE 20000



ECO-PIATTADECO

codice	W	W	V	attacco	colore	lumen	fascio	imballo
code	W	W	V	base	colour	lumen	beam	packing
21583	7	47(ERP)	220-240	GX53-I	3000°K	600	100°	10/100
21584	7	48(ERP)	220-240	GX53-I	4000°K	620	100°	10/100
21585	7	50(ERP)	220-240	GX53-I	6000°K	640	100°	10/100